

RH-PCM350Y

导热相变片

Thermal phase change

Features and Benefits

特点与优势

✳ High thermal conductivity: 3.5W/m-K
导热系数: 3.5W/M-K

✳ Phase change occurs at 45°~55°

在 45°~55° 发生相变

✳ Comes with a certain viscosity at room temperature

常温下自带一定粘性

✳ No warm-up operation



RH-PCM350Y It is a phase change material that has begun to soften at 45-55 °C. Compared with the traditional thermal conductive filling pad, the liquid filled pad can fill and cover the gaps and pits between the contact interfaces more effectively. On the other hand, it is in solid state at room temperature, providing convenience for assembly and use.

RH-PCM350Y 是一种在 45-55°C 已经开始软化的相变材料。液态时比传统的导热填充垫更能有效地填充及覆盖接触界面之间的缝隙和坑洼。另一方面，在室温环境下是固体形态，为组装及使用 时提供操作上的便利。

The above suggestions and data are based on information that we believe to be reliable. Therefore, these suggestions and data are only for reference, not as product guarantee. It is up to the customer to decide whether the product is suitable or suitable for special use. We recommend that users first determine the suitability of our materials and recommendations before using them in large quantities.

以上建议及数据均来自我们认为可靠的资料。因此这些建议及数据仅供参考，而不作为产品保证。应由客户决定产品是否合适或适用特殊用途。我们建议用户在大量使用前，首先确定我们的材料适用性和建议。

RH-PCM350Y

Property	Parameter	Unit	Test Method
Color 颜色	灰色 Gray	--	Visual
Thermal Conductivity 导热系数	3.5	W/m.k	ASTM D5470
Thickness 厚度	0.20	mm	ASTM D 751
Thickness tolerance 厚度公差	±0.02	mm	ASTM D 751
Density 密度	2.75	g/cc	ASTM D792
Volume Resistivity 体积电阻率	1.0*10 ¹¹	ohm-cm	ASTM D257
Permittivity 介电常数	3	@1M Hz	ASTM D150
Thermal impedance 热阻抗@50psi/@10psi	0.025	°C-in ² /w	ASTM D5470
Phase change temperature 相变化温度	45-55	°C	--
Fire Rating 防火等级	V-0	--	UL94
Working Temperature 工作温度	-40~125	°C	--
RoHS/REACH	Compliance	--	--

使用 ASTM D5470 测试夹具,记录值包括界面热阻,数值仅供参考。实际应用性能到所施加的表面粗糙度、平整度和压力。注:厚度公差:±10%,硬度公差:±5°,颜色/厚度/硬度均可按顾客需求调试。

Applications

典型应用

- ✳ High frequency microprocessor
- ✳ Laptop or desktop
- ✳ Computer server, memory
- ✳ Integrated chip
- ✳ LED television and lighting

- 高频微处理器
- 手提或台式电脑
- 计算机服务器, 存储器
- 集成芯片
- LED 电视和照明设备

Configurations Available

产品规格

- ✳ Flake products : according to customer requirements
片状产品: 依照顾客要求
- ✳ Die-cutting products: according to customer requirements
模切产品: 依照顾客要求

Storage & Transportation: store in a ventilated, cool and dry place, do not contact with open fire. This product is non-toxic and is stored and transported as non dangerous goods.

储存&运输: 贮存于通风、阴凉、干燥处, 不要接触明火。本产品无毒, 按非危险品贮存及运输。

Packaging: customized packaging according to customer needs.

包装: 根据客户需求定制包装。

Safety: please refer to material safety performance data (MSDS) of our company

安全: 请参阅本公司《材料安全性能数据 (MSDS) 》

Period of validity: the product is valid for 12 months

有效期: 本产品有效期为 12 个月